

# Acrylglas-GS-Rohre gegossen

## Durchmesser / Wandstärke

mm	3 mm	4 mm	5 mm	6 mm	7 mm	8 mm	10 mm	12 - 15 mm
40	*	*						
44	*	*	*					
50	*	*	*	*	*	*	*	
60	*	*	*	*	*	*	*	
64	*	*	*	*	*	*	*	
70	*	*	*	*	*	*	*	*
76	*	*	*	*	*	*	*	*
80	*	*	*	*	*	*	*	*
90	*	*	*	*	*	*	*	*
100	*	*	*	*	*	*	*	*
110	*	*	*	*	*	*	*	*
115	*	*	*	*	*	*	*	*
120	*	*	*	*	*	*	*	*
120/2100	*	*	*	*	*	*	*	*
125	*	*	*	*	*	*	*	*
134	*	*	*	*	*	*	*	*
139	*	*	*	*	*	*	*	*
150	*	*	*	*	*	*	*	*
150/2100	*	*	*	*	*	*	*	*
160	*	*	*	*	*	*	*	*
164	*	*	*	*	*	*	*	*
170	*	*	*	*	*	*	*	*
185	*	*	*	*	*	*	*	*
200	*	*	*	*	*	*	*	*
200/2100	*	*	*	*	*	*	*	*
220	*	*	*	*	*	*	*	*
230	*	*	*	*	*	*	*	*
240	*	*	*	*	*	*	*	*
250	*	*	*	*	*	*	*	*
260	*	*	*	*	*	*	*	*
300		*	*	*	*	*	*	*
300/3100		*	*	*				
300/4100		*	*					
350		*	*	*	*	*	*	
400		*	*	*	*	*	*	
457		*	*	*		*	*	
500		*	*	*	*	*	*	
650			*	*		*		

Standardlänge:

Durchmesser: 50 - 400 mm

= 2000 mm

ab 457 mm

= 2100 mm

ab 500 mm

= 2060 mm

ab 650 mm

= 2200 mm

\* auf Anfrage

**Weitere Typen, Durchmesser und Längen auf Anfrage \*\***

\*\* Bitte beachten Sie unsere wichtigen Informationen unter Startseite AGB's / wichtige Hinweise